

# CPx

Warm Air Cabinet Heater  
Natural Gas / LPG / Oil Fired Options



## Overview

Powrmatic's new ErP compliant CPx range of cabinet type heaters combine installation versatility with a range of Kw outputs to match the most stringent applications. The range can be installed in the heated space, be sited in plant rooms and specified for either vertical or horizontal installation. The CPx EA range can also be specified for external applications.

## Models Available

- CPx UF Upright Freeblowing
- CPx UD Upright Ducted
- CPx HF Horizontal Freeblowing
- CPx HD Horizontal Ducted
- CPx EA UD External Upright Ducted
- CPx EA HD External Horizontal Ducted

## Product Features

- CPx versatility is enhanced with the availability of horizontal types for applications where space and air direction is specific.
- Thirteen outputs ranging from 30kW through to 590kW in both vertical and horizontal arrangement. internal and external design and free blowing or ducted supply air, most customers requirements are covered.
- Low NOx and high energy output with highest efficiency without condensing, simple and efficient high - low burner control.
- Powrmatic working alongside market leading burner manufacturer Riello now utilise a pre-fitted and tested low NOx, high-low control " Gulliver " burner as standard. When specified the heater can be fuelled by Natural Gas, LPG or Oil.

## Specification

- CPx Drum and tube, four pass heat exchanger will be constructed as standard with a stainless steel drum combustion chamber and an aluminised or stainless steel tubular heat exchanger.
- Standard models up to CPx250 will be supplied with a T430 stainless steel drum and T304 rear drum and includes aluminised steel tubes and smoke box.

- Standard models CPx300 and above will be supplied with a T304 stainless steel drum and T304 rear drum and includes aluminised steel tubes and T304 stainless steel smoke box.
- CPx EA Drum and tube will be manufactured from stainless steel T304, this option can be specified on all units.
- Low NOx "Gulliver" high-low fire burners will be fitted as standard, gas fired modulating burners optional.
- Heaters will be supplied to run on either Gas, LPG, 35 or 28 second oil.
- Free blowing heaters will be supplied with between two and eight louvred discharge heads according to heat output.
- Ducted models are available with fan static pressure duties between 188 and 600Pa according to model and options fitted.
- Models up to 90kw will be supplied as standard 1ph, 3ph optional, all other capacities will be supplied 3ph as standard, 1ph optional on standard models 120 and 150 only.
- Soft start fan and motor control will be standard on all models 250 and above.
- Options will include, Modulating gas burner, Inverter drive, 409 stainless steel heat exchanger and Painted RAL colour of choice.
- Accessories of choice for internal heaters, side or rear inlet spigots, screened air intake, inlet filter and air dampers.
- Available accessories for EA external heaters, weatherproof inlet filter, weatherproof inlet dampers with damper motors.
- CPx control is by MC200 as standard, this will be either heater chassis mounted or remote according to model.

# Technical Performance

CPx

A1	Model		30	45	60	90(gas)	90(oil)	120	150	175	200	250	300	360	440	590					
Output		kW	30	45	60	90	90	120	150	175	200	250	290	366	440	586					
Input (nett CV)	G20 Gas	kW	32.6	47.3	65.2	97.8	n/a	127.4	163.0	190.1	217.4	269.2	304.0	399.0	479.6	638.7					
	Oil*	kW	32.0	49.2	63.6	n/a	98.2	129.5	159.5	194.9	213.2	280.7	316.1	391.6	470.8	627.0					
Old Powrmatic Reference		CP	100	150	200	300	300	400	500	600	700	800	1000	1250	1500	2000					
NOx Seasonal (Gross)		mg/kWh	56.0	58.5	59.0	65.5	65.5	67.5	69.2	65.5	84.9	97.3	tbc	tbc	tbc	tbc					
Seasonal Space Heating Energy Efficiency		% $\eta_{s,h}$	73.6%	74.7%	72.5%	74.2%	74.2%	72.8%	75.2%	72.9%	72.1%	72.5%	tbc	tbc	tbc	tbc					
Thermal Efficiencies (Nett CV)		%	Min 91.5%																		
Airflow	Volume	m <sup>3</sup> /s	0.97	0.86	1.01	2.11	1.50	2.30	3.15	3.36	4.00	4.49	5.76	6.49	7.88	10.5					
	Heads	UF / HF	No.	2	2	3	3	3	4	4	4	4	4	4	4	8	8				
		Size	mm	203	254	254	305	305	305/358	305/358	358	406	457	457	457	457	457				
	Throw	UF / HF	m	15	21	19	24	24	24	29	29	29	41	48	48	30	40				
	Fan Static	Standard	Pa	188	222	270	250	200	200	185	290	250	140	140	300	300	300				
Up-rated		Pa	250	250	400	500	450	350	400	500	500	450	500	600	600	600					
Electrics	Standard Fan	Motor	kW	1.1	1.1	1.6	1.5	2.0	2.6	3.0	4.0	4.0	4.0	7.5	11.0	11.0	15.0				
		Supply	V/ph/Hz	230/1/50						400/3/50											
		Run	amp	4.5	5.0	5.0	6.0	8.0	5.0	5.4	8.0	8.0	8.0	8.0	11.4	21.3	21.3	28.9			
	Optional Std Fan	Start	amp	8.1	17.1	16.1	25.5	28.1	12.4	23.5	23.0	23.0	28.2	50.1	127.2	127.2	182.4				
		Supply	V/ph/Hz	n/a						230/1/50	n/a										
		Run	amp	n/a						14.0	n/a										
	Uprated Fan (L.H.P.)	Start	amp	n/a						38.0	n/a										
		Motor	kW	0.75	0.75	2.2	2.2	2.2	3.0	4.0	5.5	5.5	5.5	11.0	15.0	15.0	18.5				
		Supply	V/ph/Hz	230/1/50						400/3/50											
	Optional L.H.P Fan	Run	amp	n/a						3.0	4.0	4.0	5.4	n/a				n/a			
		Start	amp	n/a						9.0	15.0	15.0	23.5	n/a				n/a			
		Supply	V/ph/Hz	n/a						400/3/50											
Fuel	Connection	Oil	BSP/Rc	3/8"	3/8"	3/8"	n/a	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	1/2"				
		Gas	BSP/Rc	1/2"	1/2"	3/4"	3/4"	n/a	3/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/2"	1 1/2"	1 1/2"	1 1/2"				
	Minimum Inlet Pressure	Nat Gas	mbar	17.5				n/a				17.5									
		LPG	mbar	37.0				n/a				37.0									
Consumption Standard Outputs	Oil	l/h	3.16	4.83	6.38	n/a	9.70	12.95	15.90	18.89	21.17	26.73	31.36	38.82	47.45	63.62					
	Nat Gas	m <sup>3</sup> /h	3.45	5.00	6.89	10.34	n/a	13.47	17.23	20.10	22.99	28.43	32.14	41.41	50.61	67.86					
	LPG	m <sup>3</sup> /h	1.34	1.98	2.64	4.01	n/a	5.31	6.64	7.72	8.84	11.00	12.84	16.00	19.56	26.23					
Overall Dimensions	UF Upright Freeblowing	Height	mm	2024	2072	2494	2585	2585	2821	2821	3054	3174	3307	3307	3657	4107	4407				
		Width	mm	669	669	744	744	744	904	904	904	904	1104	1104	1260	1330	1330				
		Depth (no burner)	mm	732	732	927	927	927	1200	1200	1399	1399	1599	1599	1915	2165	2715				
Installation Clearances	UF Upright Freeblowing	Front	mm	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000				
		Side	mm	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000				
		Blank Side	mm	150	150	150	150	150	150	150	150	150	150	150	n/a	n/a	n/a				
		Rear	mm	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000				
Flue Diameter **		mm $\emptyset$	130	130	150	150	150	150	180	180	180	200	200	250	300	300					
Combustion Air Spigot		mm $\emptyset$	150	150	150	150	150	150	150	150	150	150	150	150	175	175					
Noise Level (See Note Below)		dB(A)	56	61	61	63	63	70	62	73	74	75	77	78	80	82					
Nett Weight (See Note Below)		kg	168	173	231	241	241	341	386	530	530	556	556	1012	1380	1720					

\* **Important Note:** For full technical specification notes please refer to the product installation manual on our website at [www.powrmatic.co.uk](http://www.powrmatic.co.uk)

Powrmatic Limited  
Hort Bridge, Ilminster  
Somerset  
TA19 9PS  
tel: **+44 (0) 1460 53535**  
fax: **+44 (0) 1460 52341**  
e-mail: **info@powrmatic.co.uk**

**POWRMATIC**



Powrmatic Ireland  
45 Broomhill Close  
Tallaght  
Dublin 24  
tel: **+353 (0) 1452 1533**  
fax: **+353 (0) 1452 1764**  
e-mail: **info@powrmatic.ie**